PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

B24D 3/26, 3/34, 11/00, B24B 37/04 //
H01L 21/304

(11) International Publication Number: WO 99/62673

(43) International Publication Date: 9 December 1999 (09.12.99)

(21) International Application Number: PCT/GB99/01515

(22) International Filing Date: 1 June 1999 (01.06.99)

(30) Priority Data: 60/087,742 2 June 1998 (02.06.98) US

(71) Applicants (for all designated States except US): SCAPA GROUP PLC [GB/GB]; Oakfield House, 93 Preston New Road, Blackburn, Lancashire BB2 6AY (GB). LAM RE-SEARCH CORPORATION [US/US]; 4650 Cushing Parkway, Fremont, CA 94538 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LOMBARDO, Brian [US/US]; 11 Buckridge Drive, Amherst, NH 03031 (US). BAJAJ, Rajeev [IN/US]; 4827 Mendocino Terrace, Fremont, CA 94555 (US).

(74) Agents: PHILLIPS, Patricia, Marie et al.; Wilson Gunn M'Caw, 41-51 Royal Exchange, Cross Street, Manchester M2 7BD (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: IMPROVED POLISHING PAD WITH REDUCED MOISTURE ABSORPTION

(57) Abstract

A polishing pad or belt or other device with increased resistance to moisture absorption for improved pianarizing effectiveness and consistency. The relatively moisture resistant polishing pad contains additives to improve wetting of the pad surface for good slurry distribution.

ing the state of t

 $ho \sim 1$. The second second

The control of the co

All the second of the contract of the second of the second

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

The second of the second of the second

	•	-			the state of	,	,
AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia Juli	FI	Finland	LT	Lithuania	SK	
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
		GA	Gabon	LV	Latvia	SZ	Swaziland
AU	Australia Azerbaijan	GB	United Kingdom	MC	Monaco	TI	Chad
AZ	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TC	Togo
BA		GH	Ghana	MG	Madagascar	TJ	Tajikistan
BB	Barbados	GN	Guinea	MK	The former Yugoslav	TN	1 Turkmenistan
BE	Belgium	GR	Greece		Republic of Macedonia	TF	₹ Turkey
BF	Burkina Faso	←ĦU:	Hungary '	ML	Mali	T	Trinidad and Tobago
BG	Burlgarin	IE	Ireland	MN	Mongolia	U	
BJ	Benin		Israel	MR	Mauritania	U	G Uganda
BR	Brazil	IL IS	Iceland 1	MW	Matawi	Ū.	S . United States of America
BY	Belarus	IT IT	Italy	MX	Mexico	U	
CA	Canada		•	NE	Niger	V	
CF	Central African Republic	JP KE	Japan	NL	Netherlands	Y	
CG	Congo		Kenya	NO	Norway	ż	
CH	Switzerland	KG	Kyrgyzstan		New Zealand	_	
Cl	Cote d'Ivoire	f KP v	Democratic People's	NZ ,	Poland	•	* *
CM	Cameroon		Republic of Korea	PL PT			
CN	China .	KR	Republic of Korea		Portugal		
CU	Cuba	KZ	Kazakstan	KO	Romania		•
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	Li	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

1 - -

IMPROVED POLISHING PAD WITH REDUCED MOISTURE ABSORPTION

Cross Reference To Related Application

This is a complete application of provisional application Serial No. 60/087,742, filed June 2, 1998.

Background of the Invention

The purpose of this invention is to produce a polishing pad or belt or other device with increased resistance to moisture absorption for improved planarizing effectiveness and consistency.

Currently available polishing pads, typically polyurethane foam, are limited in effectiveness and consistency because they readily absorb moisture. In use, polishing pads are in continuous contact with aqueous slurries and cleaning solutions. Moisture absorption affects the performance of polishing pads in the following two ways:

- 1) Softening, swelling, or loss of rigidity through physical and chemical degradation, resulting in reduced planarizing effectiveness and reduced lifetime of the polishing pad,
- 2) Gradual changes in pad properties and integrity during use, resulting in unsteady and inconsistent performance.

previous attempts to make polishing pads with reduced moisture absorption or with increased resistance to degradation have been limited because the pads are too hydrophobic, resulting in poor wetting, inefficient slurry distribution, and reduced removal rates. This invention overcomes that limitation in

generally hydrophobic polishing pads through the use of hydrophilic additives.

The state of the s

out of the state of the state of the season

Summary of the Invention

This invention comprises a relatively moisture resistant polishing pad with additives to improve wetting of the pad surface for good slurry distribution.

Brief Description of the Invention

Although the descriptions of the invention refer to pads, the invention can be in any suitable form or shape, including but not limited to sheets, belts, disks, rollers and bobs.

The polishing pad matrix material can be any polymeric material or any combination of polymeric materials, including thermoplastic and cross-linked materials, that absorbs less than 4% moisture after soaking for 24 hours.

The polishing pad can include a porous structure. The porosity can be achieved by any suitable method, including but not limited to blowing, frothing, and inclusion of filled or unfilled hollow microelements. The pores can be any combination or distribution of size, shape, and quality (open or closed cell).

The polishing pad can include any type of texturing, formed naturally or by any suitable methods. The texturing can be created during the manufacturing process, or it can be created during use.

The additives suitable for improving wetting and

distribution of slurry include any type of hydrophilic additives surfactants, and relatively polar polymeric materials including but limited to polyurethanes, polyamides, and polyesters. The additives can be liquid, solid, semi-solid, or combinations of solid and liquid. The additives can be reactive or non-reactive with the other materials in the polishing pad. The additives can be located within the polymer matrix or within the pores of the polishing material. The additives can be any shape, size, or perform additional functions distribution, and can (e.g., hydrophilic hollow beads used to increase wetting and to create porosity). The additives can remain in place and wear away with the polishing material, or they can pop out or smear to coat, fill in, or otherwise improve the interaction between the pad surface

3

We Claim:

1. A relatively moisture resistant polishing pad providing sufficient wetting of a pad surface for good slurry distribution comprising a polymeric matrix material and a hydrophilic or relatively polar polymeric additive.

- 2. The pad of claim 1 wherein the pad is in the form or shape of a sheet, belt, disk, roller or bob.
- 3. The pad of claim 1 wherein the polymeric material is thermoplastic or cross-linked material, that absorbs less than 4% moisture after soaking for 24 hours.
- 4. The pad of claim 1 wherein the pad is porous having open or closed cells.
 - 5. The pad of claim 1 wherein the pad is textured.

Contract to the state of the st

- 6. The pad of claim 1 wherein the hydrophilic additive is a hydrophilic surfactant.
- 7. The pad of claim 1 wherein relatively polar polymeric additive is a polyurethane, polyamide or polyester.
- 8. The pad of claim 1 wherein the additive is liquid, solid, semi-solid, or a combination of solid and liquid.

- 9. The pad of claim 1 wherein the additive is reactive or non-reactive with the other materials in the pad.
- 10. The pad of claim 1 wherein the additive is located within the polymer matrix.
- 11. The pad of claim 4 wherein the additive is located within the pores of the pad.

and the specific and specific

- 12. The pad of claim 1 wherein the additive is a hydrophilic hollow bead used to increase wetting and to create porosity.
- 13. The pad of claim 1 wherein the additive remains in place or wears away with polishing, or pops out or smears to coat, fill in, or otherwise improve the interaction between the pad surface and a polishing slurry.

(x,y) = (x,y) + (x,y

(x,y) = 1 , (x,y) = (x,y) , (x,y) = (x,y)

and the state of t



Intern nal Application No PCT/GB 99/01515

A CLASSI	EICATION OF CUR IECT MATTER					
IPC 6	FICATION OF SUBJECT MATTER B24D3/26 B24D3/34	B24D11/00	B24B37/04	//H01L21/304		
According to	o International Patent Classification (IPC) or to both					
	SEARCHED		1 1			
IPC 6	ocumentation searched (classification system follow B24D B24B	ed by classification sym	ibois)			
Documenta	tion searched other than minimum documentation to	the extent that such do	cuments are included in	the fields searched		
Electronic d	lata base consulted during the international search	(name of data base and	, where practical, searci	(terms used)		
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT					
Category °	Citation of document, with indication, where appr	ropriate, of the relevant	oassages	Relevant to d	aim No.	
Α	US 4 613 345 A (THICKE F 23 September 1986 (1986- column 1, line 44 -colum	-09-23)	L)	1	ŧ	
A	US 4 728 552 A (JENSEN 3 1 March 1988 (1988-03-01 column 7, line 34 - line	()		1		
Furl	ther documents are listed in the continuation of box	с. Х	Patent family memb	ers are listed in annex.		
° Special c	ategories of cited documents :		-		·	
"A" docum	ent defining the general state of the art which is no dered to be of particular relevance document but published on or after the international	t	or priority date and not in	after the international filing date a conflict with the application but with the application but winciple or theory underlying the		
filing "L" docum which citatio "O" docum		"Y" c	 "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled 			
P docum	rrieans ient published prior to the international filing date but than the priority date claimed	in the art. document member of the same patent family				
Date of the	actual completion of the international search		Date of mailing of the int	ernational search report		
3	30 September 1999		07/10/1999		*	
Name and	mailing address of the ISA European Patent Office, P.B. 5818 Patentlaar NL - 2280 HV Rijswijk	1	Authorized officer	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
	Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Eschbach, D			

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNA DNAL SEARCH REPORT

armation on platent family members

PCT/GB 99/01515

	Patent document cited in search report		Publication date	Patent family member(s)	Publication date
	US 4613345	Α	23-09-1986	NONE	
	US 4728552	A	01-03-1988	NONE	
1					

Form PCT/ISA/210 (patent family annex) (July 1992

en i de la companio del companio de la companio de la companio del companio de la companio del la companio del la companio de la companio del la companio de la companio del la companio del la companio de la companio del la companio

english i mina ak air english mengan mina mangga sebengan mengan mengan kelapan di sebengan mengan m

the second